

## PATENT COOPERATION TREATY

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>F137522</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/US 00/ 11879</b>	International filing date (day/month/year) <b>16/06/2000</b>	(Earliest) Priority Date (day/month/year)
Applicant <b>ALCATEL</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

It is also accompanied by a copy of each prior art document cited in this report.

**1. Basis of the report**

a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

contained in the international application in written form.

filed together with the international application in computer readable form.

furnished subsequently to this Authority in written form.

furnished subsequently to this Authority in computer readable form.

the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2.  **Certain claims were found unsearchable** (See Box I).

3.  **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

the text is approved as submitted by the applicant.

the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,

the text is approved as submitted by the applicant.

the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

as suggested by the applicant.

because the applicant failed to suggest a figure.

because this figure better characterizes the invention.

None of the figures.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/11879

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C03C25/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C03C G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ, INSPEC, COMPENDEX

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 849 640 A (KRUISHOOP) 18 July 1989 (1989-07-18) column 2, line 12 – line 13; claims; figures ---	1-20
A	PATENT ABSTRACTS OF JAPAN vol. 013, no. 293 (C-615), 6 July 1989 (1989-07-06) & JP 01 087536 A (SUMITOMO ELECTRIC IND LTD), 31 March 1989 (1989-03-31) abstract ---	1-20
A	US 4 812 150 A (SCOTT) 14 March 1989 (1989-03-14) the whole document ---	1-20 -/-



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

19 February 2001

Date of mailing of the international search report

26/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Van Bommel, L

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/11879

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A ✓	GB 2 166 975 A (STC PLC) 21 May 1986 (1986-05-21) the whole document ---	1-20
A ✓	US 4 774 104 A (SEVERIJNS) 27 September 1988 (1988-09-27) claims; figures ---	1-20
A ✓	EP 0 202 803 A (COMMONWEALTH OF AUSTRALIA DEPARTMENT OF INDUSTRY TECHNOLOGY AND COMMERCE) 26 November 1986 (1986-11-26) claims; figures -----	1-20

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/11879

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4849640	A	18-07-1989	NL	8402124 A	03-02-1986
			DE	3575478 D	22-02-1990
			EP	0168105 A	15-01-1986
			JP	61018463 A	27-01-1986
JP 01087536	A	31-03-1989	JP	2547793 B	23-10-1996
US 4812150	A	14-03-1989	GB	2150858 A	10-07-1985
			AT	29708 T	15-10-1987
			AU	574407 B	07-07-1988
			AU	3585884 A	13-06-1985
			CA	1256398 A	27-06-1989
			DE	3466208 D	22-10-1987
			DK	579784 A	07-06-1985
			EP	0145299 A	19-06-1985
			ES	538105 D	01-11-1985
			ES	8602260 A	01-03-1986
			IN	162083 A	26-03-1988
			JP	60141650 A	26-07-1985
			KR	9100721 B	31-01-1991
			NO	844863 A	07-06-1985
			ZA	8409201 A	26-06-1985
GB 2166975	A	21-05-1986	NONE		
US 4774104	A	27-09-1988	NL	8601197 A	01-12-1987
			EP	0247659 A	02-12-1987
			JP	62273072 A	27-11-1987
EP 202803	A	26-11-1986	AU	581981 B	09-03-1989
			AU	5682286 A	20-11-1986
			BR	8602287 A	21-01-1987
			DD	244704 A	15-04-1987
			DK	222286 A	15-11-1986
			ES	554985 D	01-09-1987
			ES	8707985 A	16-11-1987
			JP	62163775 A	20-07-1987
			NO	861861 A	17-11-1986
			NZ	215951 A	28-10-1988

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number  
**WO 01/98223 A1**

(51) International Patent Classification<sup>7</sup>: **C03C 25/12**

**Bob, J.** [US/US]; 1003 Charlesmont Ct, Lenior, NC 28645 (US).

(21) International Application Number: PCT/US00/11879

(74) Agents: **HANNON, Brian, W.** et al.; Sughrue, Mion, Zinn, Macpeak & Seas, PLLC, 2100 Pennsylvania Ave., N.W., Suite 800, Washington, DC 20037-3202 (US).

(22) International Filing Date: 16 June 2000 (16.06.2000)

(81) Designated States (national): BR, CN, JP, KR, US.

(25) Filing Language: English

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(26) Publication Language: English

**Published:**


— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant (for all designated States except US): **ALCA-TEL** [FR/FR]; 54, Rue La Boetie, F-75008 Paris (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KHUDYAKOV, Igor, Vladimir** [RU/US]; 4413 Fox Trail, Hickory, NC 28601 (US). **PURVIS, Michael, B.** [US/US]; 619 41st Ave. Ct, N.W., Hickory, NC 28601 (US). **OVERTON,**



A1

(54) Title: UV-CURE OF COATINGS FOR AN OPTICAL FIBER WITH A LASER

(57) Abstract: An apparatus and method efficiently focuses laser light to a target fiber to rapidly and evenly cure a coating on the fiber and to increase a draw rate for the fiber. The laser light is expanded and refocused to a strip of light having a diameter that is a multiple of the fiber diameter. The strip of light is applied to one side of the fiber and a reflection of the strip of light is focused to a second side of the fiber to provide uniform radiation of the fiber.

**WO 01/98223 A1**

## UV-CURE OF COATINGS FOR AN OPTICAL FIBER WITH A LASER

### Field of Invention

The present invention relates to an effective method to cure a protective coating on an optical fiber with a continuous wave (cw) or a pulsed laser that permits the draw rate for an optical fiber to be increased. In particular, the method relates to aligning a laser beam on a 5 drawn optical fiber for even irradiation and cure of a coating disposed on the fiber.

### Description of Related Art

In the manufacture of an optical fiber, a glass preform rod is moved in a furnace at a controlled rate. The furnace softens the preform so that the optical fiber can be drawn from the molten end of the preform rod by a capstan.

10 Because the drawn optical fiber is susceptible to damage, a coating must be applied to the optical fiber after it is drawn from the preform rod but before contacting another surface. To provide such a protective coating, a material is applied to the fiber, which must be solidified before the drawn fiber reaches the capstan. The solidification is aided by cure techniques. A wet-on-wet draw technique is an exemplary form of drawing optical fiber 15 from a preform. The wet-on-wet draw technique comprises applying a first coating to the fiber and applying a second coating to the fiber while the first coating is still in its viscous form. Both the first and second coatings are subsequently cured. Other techniques are also known, such as applying a first coating, followed by cure of the first coating, then applying a second coating and cure of the second coating. This second technique requires additional 20 equipment to be included in the draw tower, but is simpler than the wet-on-wet draw technique which requires processing of the first coating while in its viscous form. Other techniques may also be employed, and the invention is not limited to the type of technique used.

A conventional technique for cure of the coating for optical fibers includes irradiation of the coating using a microwave-powered lamp, such as a Fusion lamp. Commonly employed Fusion lamps are H-bulb, D-bulb, and V-bulb in diameters of 9, 11 or 13 mm. However, it is impossible to focus a significant quantity of the lamp light onto the narrow fiber. In practice, only one to several percent of a Fusion lamp may be focused on the fiber element to be coated. Moreover, the energy of a heat Fusion lamp cannot be sufficiently directed making it difficult with coat the fiber in an even manner. Excessive heating effects and infrared radiation introduced by the Fusion lamp also degrade the characteristics for the coating material.

10        The application of a magnetic field often expedites the polymerization of the fiber coating, as discussed in U.S.P. 5,000,772 (Petisce). However, the bulk of the Fusion lamp makes it difficult for such a magnetic field to be applied to the fiber. To provide a magnetic field strong enough to affect the curing rate in a Fusion lamp arrangement would require a field so strong that it would reduce the microwave discharge of the Fusion lamp. The 15      intensity of the lamp becomes quenched, making it difficult to provide sufficient intensity to cure the coating. Therefore, the technique of increasing the cure rate using a magnetic field is not practicable or convenient with the use of a Fusion lamp.

20        To improve the efficiency of the curing process, a laser can be used in place of the microwave lamp. U.S.P. 4,812,150 discloses use of a laser to cure coatings by using the laser as a source of heat. However, the laser provides localized heating which will cause the fiber to bow since heating and curing on one side of the fiber will be greater than on the other. Further, excess heat may be generated due to local focusing of the laser beam, resulting in a coating with an undesirable modulus. Other known methods of applying lasers for

photocuring purposes, such as U.S.P. 4,227,907 and U.S.P. 5,761,367, suffer from similar deficiencies due to lack of directivity imparted to a laser beam.

### **Summary of Invention**

The present invention overcomes the above deficiencies by using a laser source to 5 initiate a photochemical process in the coating, and by using optical devices which produce a collimated laser beam for curing purposes. With such an arrangement, it is possible to cure a fiber coating with a laser source that is displaced from the target fiber. The displacement between the source and the target fiber mitigates the heat and infrared damage to the coating during cure. The optical devices further spread the laser about the target fiber to achieve an 10 even distribution of energy for curing purposes. An elongated beam, provided through a beam expander and plano-concave lens, permits a larger portion of the target fiber coating to be cured at one time. Since the laser source is displaced from the fiber, it becomes practical to apply a magnetic field to the target fiber having a curable coating, thereby further increasing the rate of cure by 20-40%. I.V. Khudyakov, et al., "Kinetics of 15 Photopolymerization of Acrylates Studied with a Cure Monitor and PhotoDSC", *Proceedings of SPIE*, vol. 3848, 1999, p.151-156. This further permits an increase in the draw rate for the optical fiber.

The laser beam wavelength is selected such that the laser energy is absorbed by 20 photoinitiator(s) in the coating. In a preferred embodiment, the coating has two photoinitiators, one with an absorption maximum at approximately 300 nm and one at approximately 400 nm. The use of two photoinitiators is important for wet-on-wet draw techniques.

### **Description of Preferred Embodiment**

A preferred embodiment will be discussed in detail below with reference to the sole drawing which illustrates an arrangement for directing a collimated laser beam evenly about a target fiber.

Referring to the drawing, a target fiber 1 is drawn from a preform (not shown) and is subjected to an environment to begin the coating process. The invention may be applied to any standard curing environment, including environments for applying primary and secondary coatings. As examples, an environment including a photoinitiator of 2-hydroxy-2-methyl-1-phenylpropan-1-one or 2, 4, 6-trimethylbenzoylphosphineoxide (or a combination thereof) be used.

The target fiber 1 is displaced from a laser 2. An exemplary distance is approximately ten feet. This displacement is further than conventional techniques using a Fusion lamp and provides a benefit by reducing the amount of damaging infrared heat irradiated to the target fiber. The laser source 2 can be selected from numerous types of continuous and pulsed lasers. An example of continuous wave lasers include a Beamlok Ar<sup>+</sup> manufactured by Spectra-Physics. This laser is operable to emit a number of wavelengths from  $\lambda$  333 to 351 nm in the ultraviolet range. The Ar<sup>+</sup> laser is suitable for industrial applications, having a power output of approximately 7 W. An exemplary pulsed laser includes Nd:YAG from Spectron Laser Systems. The third harmonic of the Nd:YAG laser has a wavelength of  $\lambda$  355 nm, which is the most suitable for curing of a fiber coating. However, other harmonics may also be used for curing purposes. The output power is 5W with a frequency of 10 kHz. Any high frequency UV pulsed laser is suitable. Another acceptable laser is an ultraviolet excimer XeCl laser having  $\lambda$  308 nm, which is manufactured by Lambda Physik.

Light with the above range of wavelengths is absorbed by most photoinitiators conventionally used for coating materials. However, some photoinitiators are able to absorb

energy in the visible light range (e.g. 400 nm to 800 nm), and so a laser source emitting energy in this range may also be used. For instance, a laser diode emitting light in the visible range may also be adapted to initiate polymerization. The process can be aided with the inclusion of dyes absorbing this range of light into the fiber coating. The Ar<sup>+</sup> laser can be 5 used for simultaneous excitation of two photoinitiators with an absorption maxima in the ultraviolet region. One photoinitiator has an absorption maximum closer to 300 nm, another photoinitiator has a maximum closer to 400 nm.

The use of a laser beam source also makes it possible to excite photoinitiators by monochromatic light within a more narrow wavelength (e.g.  $\pm .5$  nm). This selectivity makes 10 it possible to initiate and control polymerization for coating materials. By comparison, no such selectivity or control is possible with the Fusion lamp which excites indiscriminately across a broad range (on the order of 100 nm) of wavelengths. The fusion lamp may uncontrollably excite materials such as dyes or pigments included in the optical fiber coating.

Referring to the Figure, the laser is irradiated in the direction of a beam expander 3. 15 The collimated beam of the laser is in the form of an intense spot. If this spot were used for curing purposes, its intensity could potentially damage the target fiber as in conventional systems. Therefore, the beam expander 4 is used to distribute the collimated beam having a small diameter of approximately 2 mm into a larger diameter of one to several inches. The expanded beam is further passed through a plano-concave lens 4 and a cylindrical lens 5 to 20 focus the laser to a length of approximately 3-4 inches and having a diameter of several diameters of the target fiber. An exemplary diameter range for the striped beam is 1-3 mm. Opposite to the cylindrical lens on the other side of the fiber is a mirror 6 formed in a half-cylinder shape. The fiber is disposed in the center portion of the mirror. The mirror aids in distributing the light evenly about the target fiber.

The displacement between the laser source and the target fiber can comprise a large distance due to the collimation of the laser and the focusing provided by the optical elements. A displacement of more than 2 meters is permissible. In addition to mitigating extraneous heat effects, this displacement has the additional benefit of allowing space for a magnetic field generator (not shown) to be included in the curing arrangement. The application of the magnetic field is provided by known mechanisms and thus the details are omitted from this description.

The invention may also be implemented without the mirror 6 by disposing one or more additional laser sources about the target fiber to provide symmetrical illumination. For example, two lasers may be disposed 180 degrees apart about the target fiber or three lasers may be disposed 120 degrees apart. The inclusion of several laser sources would increase the intensity ( $\text{W/cm}^2$ ) and also the beam exposure ( $\text{J/cm}^2$ ). However, because laser sources are costly, the inclusion of the half-cylindrical mirror 6 helps minimize the cost of the curing apparatus.

Through use of a laser and basic optical devices, the laser energy can be focused precisely and uniformly on a drawn fiber. This permits efficient use of curing energy and an increase in the rate that a fiber is drawn. Draw rates at speeds more than 1000 m/min. may be possible with the arrangement described above.

Though a preferred embodiment has been discussed above in connection with the invention, it is possible for one skilled in the art to depart from the specific disclosure but remain within the spirit and the scope of the present invention.

## WHAT IS CLAIMED IS:

1. An apparatus for photocuring a coating on a fiber, comprising:
  - a laser source;
  - a beam expander for expanding an output of the laser source;
  - a first lens operable to focus an output of the beam expander on a target fiber; and

5 a concave optical element disposed on an opposite side of the target fiber relative to the beam expander and said first lens.
2. The apparatus of claim 1, wherein said first lens comprises a plano-concave lens with a planar side disposed towards said beam expander.
3. The apparatus of claim 1, wherein said laser source outputs radiation in a visible light range.
4. The apparatus of claim 3, wherein said laser source is a continuous wave laser.
5. The apparatus of claim 3, wherein said laser source is a pulsed laser.
6. The apparatus of claim 1, further comprising a magnetic field source which is operable to apply a magnetic field about said target fiber.
7. The apparatus of claim 1, wherein said laser source is disposed at least 2 meters away from said target fiber.

8. The apparatus of claim 6, wherein said laser source is a continuous wave laser emitting light in the UV range between 300 and 400 nm.

9. The apparatus of claim 1 further comprising a second lens disposed between said first lens and said concave optical element.

10. The apparatus of claim 9, wherein said second lens comprises a cylindrical lens.

11. The apparatus of claim 10, wherein said laser source is disposed at least 2 meters away from said target fiber.

12. A method of photocuring a fiber, comprising:  
expanding a laser beam to produce an expanded diameter laser beam;  
focusing the expanded diameter laser beam to a strip of light having a diameter that is larger than a diameter of the fiber onto a front side of the fiber;  
reflecting the laser beam strip of light to a rear side of the fiber.

5

13. The method according to claim 12, further comprising:  
applying a magnetic field around the fiber.

14. The method according to claim 12, wherein the laser beam continuously outputs light in a visible portion of electromagnetic spectrum.

15. The method according to claim 12, wherein the laser outputs pulses of visible light.

16. The method according to claim 12, wherein said laser beam emits in the range of 300-400 nm.


17. The method according to claim 12, wherein said laser beam emits radiation in the range of 400-800 nm.

18. The method according to claim 12, wherein a source of said laser beam is disposed at least 2 meters away from the fiber.

19. The apparatus of claim 1, wherein the laser source outputs radiation in a UV radiation range.

20. The apparatus of claim 3, wherein the laser source outputs radiation in a range of 400-800 nm.

1/1



## INTERNATIONAL SEARCH REPORT

Int'l Application No  
PCT/US 00/11879

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C03C25/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 C03C G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ, INSPEC, COMPENDEX

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 849 640 A (KRUISHOOP) 18 July 1989 (1989-07-18) column 2, line 12 - line 13; claims; figures ---	1-20
A	PATENT ABSTRACTS OF JAPAN vol. 013, no. 293 (C-615), 6 July 1989 (1989-07-06) & JP 01 087536 A (SUMITOMO ELECTRIC IND LTD), 31 March 1989 (1989-03-31) abstract ---	1-20
A	US 4 812 150 A (SCOTT) 14 March 1989 (1989-03-14) the whole document --- -/-	1-20

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

19 February 2001

Date of mailing of the international search report

26/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Van Bommel, L

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 00/11879

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 166 975 A (STC PLC) 21 May 1986 (1986-05-21) the whole document ----	1-20
A	US 4 774 104 A (SEVERIJNS) 27 September 1988 (1988-09-27) claims; figures ----	1-20
A	EP 0 202 803 A (COMMONWEALTH OF AUSTRALIA DEPARTMENT OF INDUSTRY TECHNOLOGY AND COMMERCE) 26 November 1986 (1986-11-26) claims; figures -----	1-20

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International Application No

PCT/US 00/11879

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 4849640	A 18-07-1989	NL 8402124	A	03-02-1986
		DE 3575478	D	22-02-1990
		EP 0168105	A	15-01-1986
		JP 61018463	A	27-01-1986
JP 01087536	A 31-03-1989	JP 2547793	B	23-10-1996
US 4812150	A 14-03-1989	GB 2150858	A	10-07-1985
		AT 29708	T	15-10-1987
		AU 574407	B	07-07-1988
		AU 3585884	A	13-06-1985
		CA 1256398	A	27-06-1989
		DE 3466208	D	22-10-1987
		DK 579784	A	07-06-1985
		EP 0145299	A	19-06-1985
		ES 538105	D	01-11-1985
		ES 8602260	A	01-03-1986
		IN 162083	A	26-03-1988
		JP 60141650	A	26-07-1985
		KR 9100721	B	31-01-1991
		NO 844863	A	07-06-1985
		ZA 8409201	A	26-06-1985
GB 2166975	A 21-05-1986	NONE		
US 4774104	A 27-09-1988	NL 8601197	A	01-12-1987
		EP 0247659	A	02-12-1987
		JP 62273072	A	27-11-1987
EP 202803	A 26-11-1986	AU 581981	B	09-03-1989
		AU 5682286	A	20-11-1986
		BR 8602287	A	21-01-1987
		DD 244704	A	15-04-1987
		DK 222286	A	15-11-1986
		ES 554985	D	01-09-1987
		ES 8707985	A	16-11-1987
		JP 62163775	A	20-07-1987
		NO 861861	A	17-11-1986
		NZ 215951	A	28-10-1988